


Recommended
P.C. Board
Hole Layout





Specifications

Current Rating : 2 Amps
 Insulator Resistance : 1000 Megohms min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 500V
 Operating Temperature : -40°C ~ +105°C
 Contact Material : Brass
 Insulator Material : Polyester, UL 94V-0
 Standard : Nylon 6T
 Contact Plated : Full Gold, Full Tin, Selective Plated

Order Information

Serial No. PB1 1 - 0 1 XX - X XX 0
 Terminal Type 1 : Straight Type
 Row Type 1 : Single Row
 No. of Contact per Row
 Terminal Dim. Type
 1. AL=3.0 ,L=8.7 ,C=2.0
 2. AL=2.0 ,L=8.0 ,C=2.0
 3. AL=3.0 ,L=15.0 ,C=2.0
 4. AL=2.8 ,L=7.6 ,C=2.0
 5. AL=2.8 ,L=8.8 ,C=2.0
 6. AL=4.0 ,L=12.0 ,C=2.0
 7. AL=2.5 ,L=6.5 ,C=2.0
 8. AL=3.0 ,L=8.7 ,C=1.5
 9. AL=2.3 ,L=12.0 ,C=2.0
 A. AL=2.5 ,L=14.5 ,C=2.0
 B. AL=2.0 ,L=10.6 ,C=2.0
 C. AL=3.0 ,L=8.3 ,C=1.5
 Contact Plated

Contact Plating Type		
Full Gold Plating	Duplex Plating Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
GF : Gold Flash G1 : Gold 3u" G2 : Gold 5u" G3 : Gold 10u" G4 : Gold 15u"	HF : Gold Flash, Tin 100u" H1 : Gold 3u", Tin 100u" H2 : Gold 5u", Tin 100u" H3 : Gold 10u", Tin 100u" H4 : Gold 15u", Tin 100u"	T1 : Tin 100u"

		TOLERANCE UNLESS SPECIFIED		 朝富科技股份有限公司 JOIN TEK CORPORATION CO., LTD.					
		LINEAR	ANGLE				SCALE	SHEET	VER.
		.X ± 0.25	X' ± 5'					1/1	A
		.XX ± 0.15	.X' ± 2'						
		.XXX ± 0.05	.XX' ± 1'	日期	2008.11.26				
				審核					
更改 REV.	設 變 內 容 MODIFICATION	修改 DRAWN	核准 APPROVED	製 圖	SAM				
				名稱 : Pin Header P2.0mm TITLE Single Row, Straight Type 料號 : PB11-01XX-XGFO PART NO.					