


Specifications
 Current Rating : 2 Amps
 Insulator Resistance : 1000 Megohms min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 500V
 Operating Temperature : -40°C ~ +105°C
 Contact Material : Brass
 Insulator Material : Polyester, UL 94V-0
 Standard : P.B.T
 Contact Plated : Full Gold, Full Tin, Selective Plated

Order Information

Serial No. PB2 2 - 0 2 XX - X XX 0
 Terminal Type 2 : Right Angle Type
 Row Type 2 : Dual Rows
 No. of Contact per Row
 Terminal Dim. Type
 1. AL=1.65 ,BL=3.80 ,C=3.00
 2. AL=1.00 ,BL=4.00 ,C=2.80
 3. AL=1.27 ,BL=3.20 ,C=3.00
 4. AL=1.50 ,BL=3.50 ,C=2.80
 5. AL=1.30 ,BL=4.00 ,C=3.00
 Contact Plated

Recommended
 P.C. Board
 Hole Layout



Contact Plating Type		
Full Gold Plating	Duplex Plating Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
GF : Gold Flash G1 : Gold 3u" G2 : Gold 5u" G3 : Gold 10u" G4 : Gold 15u"	HF : Gold Flash, Tin 100u" H1 : Gold 3u", Tin 100u" H2 : Gold 5u", Tin 100u" H3 : Gold 10u", Tin 100u" H4 : Gold 15u", Tin 100u"	T1 : Tin 100u"

ECN 設變	MODIFICATION 設變內容	DRAWN 修改	APPROVED 核准

.X±0.10	.X±	單位 : MM
.XX±0.05	.XX±	料號 :
.XXX±0.03	.XXX±	PB22-02XX-XGFO
本藍圖為朝富科技股份有限公司所有.未經本公司書面許可,嚴禁印製		日期 : 2006/01/19
		審核 :
		製圖 : Sam

朝富科技股份有限公司 JOIN TEK JOIN TEK CORPORATION CO.,LTD.		
名稱 : Pin Header P2.0mm		
Dual Rows, Right Angle Type		
圖號 : PB22-02XX-01		
SCALE	SHEET	REV.
1/1	A	A