



Recommended  
P.C.Board  
Hole Layout



Contact Plating Type		
Full Gold Plating	Duplex Plating Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
GF : Gold Flash	HF : Gold Flash, Tin 100u"	T1 : Tin 100u"
G1 : Gold 3u"	H1 : Gold 3u", Tin 100u"	
G2 : Gold 5u"	H2 : Gold 5u", Tin 100u"	
G3 : Gold 10u"	H3 : Gold 10u", Tin 100u"	
G4 : Gold 15u"	H4 : Gold 15u", Tin 100u"	

### Specifications

Current Rating : 1 Amps  
 Insulator Resistance : 1000 Megohms min.  
 Contact Resistance : 20 m ohms max.  
 Dielectric Withstanding : AC 300V  
 Operating Temperature : -40°C ~ +105°C  
 Contact Material : Phosphor Bronze  
 Insulator Material : Polyester, UL 94V-0  
 Standard : Nylon-6T  
 Contact Plated : Full Gold, Full Tin, Selective Plated

### Order Information

Serial No. SC6 1 - 0 1 XX - X XX 0  
 Terminal Type 1 : Straight Type  
 Row Type 1 : Single Row  
 No. of Contact per Row  
 Terminal Dim. Type 0 : A=2.80  
 1 : A=1.80  
 Contact Plated  
 Packing List  
 0 : In Box  
 A : In Tube  
 B : W/Cap In Tube  
 C : W/Film In Tube  
 D : W/Cap In Tape & Reel  
 E : W/Film In Tape & Reel

.X±0.25	.X±	單位 : MM	朝富科技股份有限公司 名稱 : Female Header P1.27X1.27 TITLE : Profile : 3.4mm, Single Row 圖號 : SC61-01XX DWG No.							
.XX±0.15	.XX±	料號 :								
.XXX±0.05	.XXX±	SC61-01XX-0XX0								
本藍圖為朝富科技股份有限公司所有, 未經本公司書面許可, 嚴禁印製			日期 : 2005/11/11 審核 : 製圖 : Sam							
ECN 設變	MODIFICATION 設變內容	DRAWN 修改	APPROVED 核准	<table border="1"> <tr> <td>SCALE</td> <td>SHEET</td> <td>REV.</td> </tr> <tr> <td></td> <td>1/1</td> <td>B</td> </tr> </table>	SCALE	SHEET	REV.		1/1	B
SCALE	SHEET	REV.								
	1/1	B								