



Specifications

Current Rating : 1 Amps
 Insulator Resistance : 5000 Megohms min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 500V
 Operating Temperature : -40°C ~ +105°C
 Contact Material : Brass
 Insulator Material : Polyester, UL 94V-0
 Standard : LCP BLACK
 Contact Plated : Full Gold Flash

Order Information

PC3 3 - X 1 XX - X XX X

Serial No. _____
 Terminal Type _____
 3 : SMT Type
 Pin Layout Type _____
 A : A Type
 B : B Type
 Row Type _____
 1 : Single Rows
 No. of Contact per Row _____
 Terminal Dim. Type _____
 0. A=2.50 ,b=2.30 ,c=1.00 ,d=4.60
 1. A=4.83 ,b=3.81 ,c=2.00 ,d=5.00
 2. A=... ,b=... ,c=... ,d=...
 Contact Plated _____

Packing List
 0 : In Bag
 A : In Tube
 B : W/Cap In Tube
 C : W/Film In Tube
 D : W/Cap In Tape & Reel
 E : W/Film In Tape & Reel

Contact Plating Type		
	Duplex Plating	
Full Gold Plating	Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
CF : Gold Flash G1 : Gold 3u" G2 : Gold 5u" G3 : Gold 10u" G4 : Gold 15u"	HF : Gold Flash, Tin 100u" H1 : Gold 3u", Tin 100u" H2 : Gold 5u", Tin 100u" H3 : Gold 10u", Tin 100u" H4 : Gold 15u", Tin 100u"	T1 : Tin 100u"

TOLERANCE UNLESS SPECIFIED			
LINEAR		ANGLE	
.X ± 0.25	X' ± 5'		
.XX ± 0.15	.X' ± 2'		
.XXX ± 0.08	.XX' ± 1'		
日期	2014.05.06		
審核			
更改 REV.	變更內容 MODIFICATION	修改 DRAWN	核准 APPROVED
		製圖	Jason

朝富科技股份有限公司
 JOIN TEK CORPORATION CO., LTD.

SCALE	SHEET	VER.
	1/1	A

名稱 : Pin Header P1.27mm SMT
 TITLE
 料號 : PC33-X1XX-XGFX
 PART NO.