

Specifications


Current Rating : 3 Amps
 Insulator Resistance : 1000 Megohms min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 600V
 Operating Temperature : -40°C ~ +105°C
 Contact Material : Brass
 Insulator Material : Polyester, UL 94V-0
 Standard : 6T
 Contact Plated : Full Gold, Full Tin, Selective Plated

Order Information


Serial Type PA1 2 - 0 1 XX - X XX 0
 Terminal Type 2 : Right Angle Type
 Row Type 1 : Single Row
 No. of Pin per Row
 Terminal Dim.

1. AL=1.5 ,BL=3.0 ,C=6.0
2. AL=3.0 ,BL=3.0 ,C=2.5
3. AL=0.5 ,BL=3.0 ,C=5.0
4. AL=3.68 ,BL=8.00 ,C=6.00
5. AL=1.00 ,BL=3.00 ,C=7.00
6. AL=1.50 ,BL=6.00 ,C=3.00
7. AL=3.50 ,BL=2.50 ,C=3.00
8. AL=0.5 ,BL=3.80 ,C=3.10
9. AL=1.65 ,BL=1.50 ,C=4.50
- A. AL=1.00 ,BL=3.00 ,C=8.00

Recommended
 P.C. Board
 Hole Layout



Contact Plating Type		
Full Gold Plating	Duplex Plating Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
GF : Gold Flash G1 : Gold 3u" G2 : Gold 5u" G3 : Gold 10u" G4 : Gold 15u"	HF : Gold Flash, Tin 100u" H1 : Gold 3u", Tin 100u" H2 : Gold 5u", Tin 100u" H3 : Gold 10u", Tin 100u" H4 : Gold 15u", Tin 100u"	T1 : Tin 100u"

				TOLERANCE UNLESS SPECIFIED		 朝富科技股份有限公司 JOIN TEK CORPORATION CO., LTD.						
				LINEAR	ANGLE							
				.X ± 0.25	X.' ± 5'	<table border="1"> <tr> <th>SCALE</th> <th>SHEET</th> <th>VER.</th> </tr> <tr> <td></td> <td>1/1</td> <td>A</td> </tr> </table>	SCALE	SHEET	VER.		1/1	A
SCALE	SHEET	VER.										
	1/1	A										
				.XX ± 0.15	.X' ± 2'							
				.XXX ± 0.05	.XX' ± 1'							
				日期	2006.01.20	名稱 : Pin Header P2.54mm TITLE Single Row, Right Angle Type						
				審核								
更改 REV.	設變內容 MODIFICATION	修改 DRAWN	核准 APPROVED	製圖	SAM	料號 : PART NO. PA12-01XX-XXX0						