


Specifications

Current Rating : 1 Amps
 Insulator Resistance : 1000 Megohms min.
 Contact Resistance : 30 m ohms max.
 Dielectric Withstanding : AC 500V(1 min)
 Operating Temperature : -40°C ~ +85°C
 Contact Material : Brass
 Insulator Material : Polyester, UL 94V-0
 Standard :
 Contact Plated : Full Gold Flash

Order Information

Serial No. PD3 1 - 0 1 XX - X XX 0
 Terminal Type 1 : Straight Type
 Row Type 1 : Single Rows
 No. of Contact per Row
 Terminal Dim. Type
 1. AL=2.80 ,BL=1.20 ,D=1.00
 2. AL=1.8 ,BL=1.20 ,D=1.00
 Contact Plated
 Packing List
 O. In Bag
 A. In Tube
 B. With Cap In Tube
 D. With Cap In Tape&Reel

Contact Plating Type		
Full Gold Plating	Duplex Plating Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
GF : Gold Flash G1 : Gold 3u" G2 : Gold 5u" G3 : Gold 10u" G4 : Gold 15u"	HF : Gold Flash, Tin 100u" H1 : Gold 3u", Tin 100u" H2 : Gold 5u", Tin 100u" H3 : Gold 10u", Tin 100u" H4 : Gold 15u", Tin 100u"	T1 : Tin 100u"

TOLERANCE UNLESS SPECIFIED		 朝富科技股份有限公司 JOIN TEK CORPORATION CO., LTD.		
LINEAR	ANGLE	SCALE	SHEET	VER.
.X ± 0.30	X' ± 5'		1/1	A
.XX ± 0.20	.X' ± 2'			
.XXX ± 0.10	.XX' ± 1'			
日期	2015.08.25	名稱 : Pin Header P1.0mm		
審核		TITLE Single Rows, DIP Type		
更改 REV.	變更內容 MODIFICATION	修改 DRAWN	核准 APPROVED	製圖 JASON
		料號 : PD31-01XX-XGFO		PART NO.