



Electrical Characteristics:
 Current rating: 0.5A AC/DC
 Voltage rating: 50V AC/DC
 Temperature range: -25°C~+85°C
 Withstand Voltage: 200V AC/Minute
 Contact Resistance: 20mΩ
 Insulation resistance: 500MΩ
 Relative Humidity: 93%+40°C

Material Description:
 Terminal: Phosphor Bronze Tin-plated
 Fitting Nail: Brass Tin-Plated
 Housing: Thermoplastic (UL94V-0)
 Slider: Thermoplastic (UL94V-0)

ORDERING CODE

JSF5 3 - 2 X X - X 1 1 X - X

FFC\FPC
 PITCH 0.5mm
 HORIZONTAL
 CONTACT TYPE
 2:LOWER CONTACT

NO. OF CONTACTS
 06-60 PIN
 HOUSING & ACTUATOR MATERIALS
 9:HOUSING LCP, ACTUATOR LCP
 <BLACK>UL 94V-0

PLANTING
 A: MATTE TIN 100u" MIN, OVER
 50u"MIN NI ON CONTACT

PACKING TYPE
 1:TUBE
 2:REEL

HOLDDOWN TYPE
 1:HOLDDOWN TYPE 1.
 TAIL LENGTH
 1:TAIL LENGTH 0.70mm.

PIN数	DIM=A	DIM=B	DIM=C	DIM=D	PIN数	DIM=A	DIM=B	DIM=C	DIM=D
60P	34.40	31.50	29.50	30.60	32P	20.40	17.50	15.50	16.60
59P	33.90	31.00	29.00	30.10	31P	19.90	17.00	15.00	16.10
58P	33.40	30.50	28.50	29.60	30P	19.40	16.50	14.50	15.60
57P	32.90	30.00	28.00	29.10	29P	18.90	16.00	14.00	15.10
56P	32.40	29.50	27.50	28.60	28P	18.40	15.50	13.50	14.60
55P	31.90	29.00	27.00	28.10	27P	17.90	15.00	13.00	14.10
54P	31.40	28.50	26.50	27.60	26P	17.40	14.50	12.50	13.60
53P	30.90	28.00	26.00	27.10	25P	16.90	14.00	12.00	13.10
52P	30.40	27.50	25.50	26.60	24P	16.40	13.50	11.50	12.60
51P	29.90	27.00	25.00	26.10	23P	15.90	13.00	11.00	12.10
50P	29.40	26.50	24.50	25.60	22P	15.40	12.50	10.50	11.60
49P	28.90	26.00	24.00	25.10	21P	14.90	12.00	10.00	11.10
48P	28.40	25.50	23.50	24.60	20P	14.40	11.50	9.50	10.60
47P	27.90	25.00	23.00	24.10	19P	13.90	11.00	9.00	10.10
46P	27.40	24.50	22.50	23.60	18P	13.40	10.50	8.50	9.60
45P	26.90	24.00	22.00	23.10	17P	12.90	10.00	8.00	9.10
44P	26.40	23.50	21.50	22.60	16P	12.40	9.50	7.50	8.60
43P	25.90	23.00	21.00	22.10	15P	11.90	9.00	7.00	8.10
42P	25.40	22.50	20.50	21.60	14P	11.40	8.50	6.50	7.60
41P	24.90	22.00	20.00	21.10	13P	10.90	8.00	6.00	7.10
40P	24.40	21.50	19.50	20.60	12P	10.40	7.50	5.50	6.60
39P	23.90	21.00	19.00	20.10	11P	9.90	7.00	5.00	6.10
38P	23.40	20.50	18.50	19.60	10P	9.40	6.50	4.50	5.60
37P	22.90	20.00	18.00	19.10	9P	8.90	6.00	4.00	5.10
36P	22.40	19.50	17.50	18.60	8P	8.40	5.50	3.50	4.60
35P	21.90	19.00	17.00	18.10	7P	7.90	5.00	3.00	4.10
34P	21.40	18.50	16.50	17.60	6P	7.40	4.50	2.50	3.60
33P	20.90	18.00	16.00	17.10					

				TOLERANCE UNLESS SPECIFIED				朝富科技股份有限公司		
				LINEAR		ANGLE		JOIN TEK JOIN TEK CORPORATION CO., LTD.		
				.X	±0.20	X.*	±5°			
				.XX	±0.15	.X.*	±2°			
				.XXX	±0.10	.XX	±1°			
				日期	2014.12.22			SCALE SHEET VER.		
				審核	JASON			名稱: FPC CONNECTOR		
				製圖	JAY			TITLE: PITCH=0.5mm H2.0		
更改	說明內容	修改	核准					料號: JSF53-2XX-911X-X		
REV.	MODIFICATION	DRAWN	APPROVED					PART NO.		