



PCB LAYOUT

规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

原材料:Material:

1. 塑胶: Housing:
High Temperature Thermoplastics,
UL 94V-0 PBT White
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: C2680

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
2. 外壳: Shell:
Nickel Plating

				TOLERANCE UNLESS SPECIFIED		 朝富科技股份有限公司 JOIN TEK CORPORATION CO., LTD.						
				LINEAR	ANGLE				SCALE		SHEET	VER.
				.X ± 0.30	X° ± 5°				1/1		1/1	A
				.XX ± 0.20	.X° ± 2°							
				.XXX ± 0.10	.XX° ± 1°							
				日期	2020.04.08		名稱: USB A/F 180度 DIP 總長 15mm					
				審核	JASON		TITLE					
更改 REV.	設 變 內 容 MODIFICATION	繪 製 DRAWN	核 准 APPROVED	製 圖	BEAR		料號: U224-415B-2130 PART NO.					