



Notes:

1.electrical test:

- (1)100% OPEN short and mis-wire test.
- (2)Contact Resistance : 5Ω MAX.
- (3)Insulation Resistance : 10MΩMin
- (4)Contact Voltage :DC300V

2. Data Transmission Rate: Gen 2 (10 Gbps)

No.	ITEM	BILL OF MATERIAL	QTY	更改 REV.	設 變 內 容 MODIFICATION	修改 DRAWN	核准 APPROVED	TOLERANCE UNLESS SPECIFIED		日期 2023.08.08	審核 製圖 李世寶	名稱 : USB 3.1 C TO C TPE VW-1 TITLE	料號 : USBC-8787-LXXX PART NO.	
								LINEAR	ANGLE					
5	INNER MODING	TPE		AR				.X ± 0.30	X.° ± 5°			UNIT	SHEET	VER.
4	INNER MODING	PE		AR				.XX ± 0.20	.X° ± 2°			1/1	A0	
3	END B	USB 3.1 TYPE C PLUG SOLDER 3u" (6-PB12R-01-C2)		1 PC				.XXX ± 0.10	.XX° ± 1°					
2	END A	USB 3.1 TYPE C PLUG SOLDER 3u" (6-PB12R-01-C2)		1 PC										
1	Cable	USB 3.1 (7/0.06TA*1PR+EAM)*4+(7/0.06TA*1PR+AM)+7/0.06TA*4C+7/0.06TA*2C+AB90% TPE BLACK VW-1 OD=4.6MM		AR	A0	New Release								

朝富科技股份有限公司
JOIN TEK JOIN TEK CORPORATION CO., LTD.

UNIT SHEET VER.
1/1 A0

名 稱 : USB 3.1 C TO C TPE VW-1
TITL E
料 號 : USBC-8787-LXXX
PART NO.